



# Superdual T



## TECHNICAL SPECIFICATION

<b>ENGINE</b>	
ENGINE	Liquid Cooled, Single Cylinder, 4 Stroke, 4 Valves
DISPLACEMENT	600 cc
POWER	54 Bhp @ 7500 Rpm
TORQUE	55 Nm @ 6250 Rpm
COOLING	Liquid cooled
<b>TRANSMISSION</b>	
TRANSMISSION	Hydraulic Clutch, 6-speed constant mesh
<b>SUSPENSION</b>	
FRONT SUSPENSION	FAST ACE "Upside- Down" telescopic hydraulic fork with rebound damping adjustment
REAR SUSPENSION	SACHS Progressive "Soft Damp" type with single hydraulic shock absorber; spring preload adjustment, rebound damping adjustment
<b>BRAKE</b>	
FRONT BRAKE	Brembo, Single floating disc with Ø 300 mm diameter with ABS.
REAR BRAKE	Brembo, Single steel disc with Ø 220 mm diameter, with ABS
<b>WHEELS</b>	
FRONT TYRE	100/80 - ZR 19
REAR TYRE	140/80 - ZR 17
<b>WEIGHT &amp; CAPACITY</b>	
KERB WEIGHT	169 Kg
GROUND CLEARANCE	180 mm
FUEL TANK CAPACITY	18 Liters