



ENGINE

Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C"
Total displacement	798 cm ³ (48.7 cu. in.)
Compression ratio	13.3:1
Starting	Electric
Bore x stroke	79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)**	108.8 kW (148 hp) at 13.000 r.p.m.
Max. torque - r.p.m.	88 Nm (8.97 kgm) at 10.600 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Integrated ignition - injection system MVICS (Motor & Vehicle Integrated Control System) with six injectors Engine control unit Eldor EM2.0, throttle body full drive by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire Torque control with four maps, Traction Control with eight levels of intervention MV EAS (Electronically Assisted Shift)
Electronic quick shift	
Clutch	Wet, multi-disc slipper clutch
Transmission	Cassette style; six speed, constant mesh
Primary drive	19/36
Gear ratio	
First gear:	13/37
Second gear:	16/34
Third gear:	18/32
Fourth gear:	19/30
Fifth gear:	21/30
Sixth gear:	22/29
Final drive ratio	17/41

ELECTRICAL EQUIPMENT

Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 8.6 Ah

DIMENSIONS AND WEIGHT

Wheelbase	1380 mm (54.33 in.)
Overall length	2060 mm (81.01 in.)
Overall width	725 mm (28.54 in.)
Saddle height	805 mm (31.69 in.)
Min. ground clearance	125 mm (4.92 in.)
Trail	99 mm (3.89 in.)
Dry weight	173 kg (381.4 lbs.)
Fuel tank capacity	16,5 l (4.36 U.S. gal.)

PERFORMANCE

Maximum speed*	269.0 km/h (167.1 mph)
----------------	------------------------

FRAME

Type	ALS Steel tubular trellis
Rear swing arm pivot plates material	Aluminium alloy

FRONT SUSPENSION

Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	125 mm (4.92 in.)

REAR SUSPENSION

Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	123 mm (4.84 in.)

BRAKES

Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type monobloc, with 4 pistons Ø 34 mm (Ø 1.34 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Bosch 9 Plus with Race Mode and RLM (Rear wheel Lift-up Mitigation)

WHEELS

Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 5.50 " x 17 "

TYRES

Front	120/70 - ZR 17 M/C (58 W)
Rear	180/55 - ZR 17 M/C (73 W)

FAIRING

Material	Thermoplastic
----------	---------------

EQUIPMENT

Anodized aluminum mirror caps kit
 Billet aluminum Brake/Clutch levers
 Billet aluminum "Sport" License Plate Holder - Billet aluminum Foot peg kit
 Fiberglass rear seat cover

INCLUDED ACCESSORIES

Dedicated Bike cover - Rear paddock stand



KIT RACE VERSION



STREET VERSION

* Top speed attained on closed course.

** Limited power versions available on demand.